

TUBI QUADRI NERI, DECAPATI E ZINCATI

SQUARE WELDED TUBE FROM HOT, PICKLED AND GALVANIZED STRIP

SEZIONE SECTION	SPESSORE (mm) THICKNESS (mm)								
D. (mm)	1,5	2	2,5	3	4	5	6	8	10
	Kg/m								
15x15	0,59	0,74							
20x20	0,83	1,05	1,25	1,42					
25x25	1,06	1,36	1,64	1,89					
30x30	1,30	1,68	2,03	2,36					
35x35	1,53	1,99	2,42	2,83	3,57				
40x40	1,77	2,31	2,82	3,30	4,20	4,99			
45x45	2,00	2,62	3,21	3,77	4,83	5,77			
50x50	2,24	2,93	3,60	4,25	5,45	6,56			
60x60		3,56	4,39	5,19	6,71	8,13			
70x70		4,19	5,17	6,13	7,97	9,70			
80x80		4,82	5,96	7,07	9,22	11,27	13,21		
90x90		5,45	6,74	8,01	10,48	12,84	15,10		
100x100		6,07	7,53	8,96	11,73	14,41	16,98	21,39	
110x110				9,90	12,99	15,98	18,87	23,90	28,70
120x120			9,04	10,84	14,25	17,55	20,75	26,41	31,84
130x130				11,98	15,85	19,65	23,39	30,68	37,72
140x140				12,72	16,76	20,69	24,52	31,43	38,12
150x150				13,67	18,01	22,26	26,40	33,95	41,26
175x175				16,02	21,15	26,18	31,11	40,23	49,11

TUBI OVALI DECAPATI E ZINCATI

OVAL WELDED TUBE FROM PICKLED AND GALVANIZED STRIP

DIMENSIONI DIMENSIONS	SPESSORE THICKNESS		
	1	1,2	1,5
	Kg/m		
30x15	0,59	0,70	0,87
50x10	0,86	1,04	1,30

TUBI ANTIROTAZIONE

GROOVED WELDED TUBE FROM HOT AND GALVANIZED STRIP

SEZIONE SECTION	SPESSORE THICKNESS		
	2	2,5	3
	Kg/m		
48	2,38	2,98	3,58
60	3,01	3,77	4,52